

NOTICE INVITING QUOTATION

Date: 15/11/2017

Sealed item rate quotation are hereby invited from the approved contractor enlisted with CPWD, MES, Railways and working contractor of Delhi University for Providing and laying sewerline, flooring and misc. work near canteen at Satyawati College, Ashok Vihar, Phase-III, Delhi.

Name of work: Providing and laying sewerline, flooring and misc. work near canteen at Satyawati College, Ashok Vihar, Phase-III, Delhi.

Estimated Cost: Rs.3,86,634/-

Cost of Tender: Rs.500/- (non-refundable) in form of DD in favor of **'Principal, Satyawati College'**.

Time period for completion of the work: 2 months from the seventh day of issue of award letter/work order.

Date of receiving of tender document upto: 08.12.2017 at 2.30 p.m.

Date of opening tender document: 08.12.2017 at 3.30 p.m.


Earnest Money: Rs.7,500/- in form of CDR, DD in favor of **'Principal, Satyawati College'**.

Tender opening/receiving authority: Principal, Satyawati College, Ashok Vihar, Delhi

Undertaking:

I/We hereby quote item rate/percentage rate _____ above/below/ at par on the estimated cost of Rs.3,86,634/-

Signature of Contractor


Signature of Principal

I/We hereby undertake our agency have not been black listed/debarred in any government/semi-government organization since last three years.

Signature of Contractor

Conditions:

1. No conditional tender will be accepted
2. College authority reserves the right to accept or reject any or all tenders without assigning any reason thereof.
3. CPWD specification will be followed with up-to-date correction slip.
4. Rate quoted will be in figure and words.
5. 1.5% water charge will be recovered from the gross amount of work done.
6. No deviation/extra item/substitute item shall be carried out without the approval/sanctioning of the competent authority.
7. Payment will be made after due satisfaction of competent authority.
8. Taxes as applicable from time to time will be deducted from the gross amount of bill.
9. The material used in the work got approved from the competent authority. Without sample approval the work seems to be rejected and no payment will be made for.
10. The tender papers will be considered with relevant documents like registration of contractor, PAN card, GST.

ESTIMATE

Name of Work: Providing and laying sewerline, flooring and misc work near canteen at Satyawati College, Ashok Vihar, Phase-III, Delhi

S.No.	Description	Quantity	Unit	Rate	Amount
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed. All kinds of soil.	6.00	cum		
2	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m :All kinds of soil. Pipes, cables etc. exceeding 300 mm dia but not exceeding 600 mm.	42.00	metre		
3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size)	10.00	cum		
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size).	6.00	cum		
5	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:6 (1 cement : 6 coarse sand)	3.00	cum		
6	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works	1,150.00	kg		
7	15 mm cement plaster on rough side of single or half brick wall of mix :1:6 (1 cement: 6 coarse sand).	50.00	sqm.		

8	Finishing walls with textured exterior paint of required shade :New work (Two or more coats applied @ 3.28 ltr/10 sqm) over and including priming coat of exterior primer applied @ 2.20kg/10 sqm.	100.00	sqm.		
9	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work.	50.00	sqm.		
10	Providing and laying non-pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete :300 mm dia. R.C.C. pipe.	42.00	metre		
11	Constructing brick masonry road gully chamber 45x45x77.5 cm with bricks in cement mortar 1:4 (1 cement : 4 coarse sand) with precast R.C.C. vertical grating complete as per standard design :With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	1.00	each		
12	Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame o f 300 x300 mm size (inside) the weight of cover to be not less than 4.50 kg and frame to be not less than 2.70 kg as per standard design:100x100 mm size P typeWith common burnt clay F.P.S. (non modular) bricks of class designation 7.5.	1.00	each		
13	Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) with R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design : Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) : With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	6.00	each		

11	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	10.00	cum		
12	Providing and laying factory made chamfered edge Cement Concrete paver blocks of required strength, thickness & size/shape, made by table vibratory method, to attain superior smooth finish using PU or equivalent moulds, laid in required Grey colour & pattern over 50mm thick compacted bed of coarse sand, compacting and proper embedding / laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with jamuna sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand in footpath, parks, lawns, drive ways or light traffic parking etc. all complete as per manufacturer's specifications & direction of Engineer -in-Charge: (a) 80 mm thick c.c. paver block of M-30 grade with approved color design and pattern.	100	sqm.		
TOTAL					