

NOTICE INVITING QUOTATION

Date: 23.05.2017

Sealed item rate quotation are hereby invited from the approved contractor enlisted with CPWD, MES, Railways and working contractor of Delhi University for Aluminums and false ceiling work of recreation room of at Satyawati College, Ashok Vihar, Phase-III, Delhi.

Name of work: Aluminums and false ceiling work of recreation room of at Satyawati College, Ashok Vihar, Phase-III, Delhi.

Estimated Cost: ₹ 1,99,638/-

Time period for completion of the work: 20 days from the seventh day of issue of award letter/work order.

Date of receiving of tender document : 07.06.2017 at 3.00 p.m.

Date of opening tender document: 07.06.2017 at 3.30 p.m.

Earnest Money: ₹4,000/- in form of CDR, DD in favor of '**Principal, Satyawati College**'.

Tender opening/receiving authority: Principal, Satyawati College, Ashok Vihar, Delhi

Undertaking:

I/We hereby quote item rate/percentage rate _____ above/below/ at par on the estimated cost of ₹ 1,99,638/-

Signature of Contractor

Signature of Principal

I/We hereby undertake our agency have not been black listed/debarred in any government/semi-government organization since last three years.

Signature of Contractor

Conditions:

1. No conditional tender will be accepted
2. College authority reserves the right to accept or reject any or all tenders without assigning any reason thereof.
3. CPWD specification will be followed with up-to-date correction slip.
4. Rate quoted will be in figure and words.
5. 1.5% water charge will be recovered from the gross amount of work done.
6. No deviation/extra item/substitute item shall be carried out without the approval/sanctioning of the competent authority.
7. Payment will be made after due satisfaction of competent authority.
8. Taxes as applicable from time to time will be deducted from the gross amount of bill i.e. VAT 4%, Income Tax 2%, Work Labour Cess 1%.
9. The material used in the work got approved from the competent authority. Without sample approval the work seems to be rejected and no payment will be made for.
10. Electrical works are to be carried out through license holder.
11. The tender papers will be considered with relevant documents like registration of contractor, PAN card, VAT, Service Tax etc (if applicable).

Name of Work: Aluminium and false ceiling work of recreation room at Satyawati College, Ashok Vihar, hase-III, Delhi

S.No.	Description	Quantity	Unit	Rate	Amount
1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion Powder coated aluminium (minimum thickness of powder coating 50 micron)	150	kg		
2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron)	140	kg		
3	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :100x10 mm	32	each		
4	Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. complete as per direction of Engineerin-charge.Powder coated minimum thickness 50 micron aluminium	32	each		
5	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 4.0 mm thickness	23	sqm.		

S.No.	Description	Quantity	Unit	Rate	Amount
6	<p>Providing and fixing tiled false ceiling of approved materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x 1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottomexposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge. 12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side, having an NRC (Noise Reduction Coefficient) of 0.79, with 50 mm resin bonded glass wool backing.</p>	32	sqm.		
TOTAL					