

सत्यवती महाविद्यालय Satyawati College

(दिल्ली विश्वविद्यालय) (University of Delhi) NAAC ACCREDITED 'A+' GRADE



Ref. No. S.C. Adam 523 2025

Date - 10/10/2025

Notice for Inviting Spot Quotations

Percentage rate spot quotations are here by invited from contractors enlisted with CPWD, MES, Railways and working contractors of University of Delhi for the work of "Repair of toilets and kitchen at staff quarter Type IV allotted to Mr. Ashutosh Pandey at Satyawati College" So as to reach the office of the undersigned up to 1.00 PM on 13.10.2025.

Financial Bid/Estimate is attached as Annexure-A

Conditions:

- 1. Please attach proof of enlishment, PAN Number etc.
- 2. The work is to be carried out as per CPWD specifications.
- 3. The time allowed completing the work 5 days.
- The rates quoted should be inclusive of all taxes and duties & should be written both in words and figure.
- 5. The contractor should see the site before quoting the rate.
- Undersigned reserves the right to reject any or all the quotation without assigned any reason thereof.

Annexure-A

S.No.	Description of items	Qty.	Unit	Rate	Amount
1	Providing and fixing 1st quality ceramic glazed wall tiles conforming to Is: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortan 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.		sqm	1268	13947.45
2	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	11	sqm	73.4	807.4
3	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 10 km for all lifts, complete as per directions of Engineer-in-charge.	5	sqm	494.1	2470.5
4	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 20 mm nominal dia Pipes	15	metre	335	5025
5	P/F CP health faucet with flexiable pipe complete	1	each	1000	1000
6	Providing and fixing uplasticised PVC connection pipe with brass unions : 45 cm length	10	each	121.9	1219
7	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15 mm nominal bore	9	each	574.3	5168.7
8	Providing and fixing C.P. brass pillar cock (ISI make) 15 mm nominal bore.	2	each	1090.1	2180.18
9	Providing and fixing CP cap for bib cock/ angle valve etc complete as per direction of Engineer-in-charge	16	each	38.26	612.16
10	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. Flexible pipe 32 mm dia	3	each	119.55	358.65
11	Providing and fixing CP Trap Jali of approved make etc complete	9	each	139.11	1251,99

18	P/F two way bib cock CP brass of approved quality	-	Cacii	1230	49654.43
17	Repair of flushing cistern with Syphon, handle, ballcock etc complete	2	each	1200	2400
16	Providing and fixing CP brass Waste Coupling for wash basin and sink, of approved quality 32 mm dia	3	each	450	1350
15	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:	2	each	2196.1	4392.1
14	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. 15 mm nominal bore	2	each	670.45	1340.9
13	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms	2	each	168.35	336.7
12	Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms.	6	each	798.95	4793.7